

VARIO*fit*

The perfect form
of transport



colours.



Tubular steel truck, RAL 7016

Article no.		Dimension mm			Toe plate mm		Weight kg	Load cap. kg	Wheel diam. mm
		W	D	H	w	d			
sk-710.015/AG	P	570	530	1105	320	250	12.5	200	260 x 85
sk-710.016/AG	SR	570	530	1105	320	250	14.5	200	260 x 65

P = Pneumatic tyres, SR = Solid-rubber tyres

Pushbar trolleys

Pushbar trolleys

Modular system; Base structure with innovative frame section; Load surface of wood-based board, surface coated in dark grey; Trolleys powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard; 2 **EasySTOP** swivel castors and 2 fixed castors.



Pushbar trolley, RAL 7016

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.100/AG	975	500	975	880	500	25.0	400	160 x 40
sw-600.100/AG	1125	600	1015	1030	600	29.5	500	200 x 40
sw-700.100/AG	1125	700	1015	1030	700	33.5	500	200 x 40
sw-800.100/AG	1325	800	1015	1230	800	37.0	500	200 x 40

EasySTOP swivel castors and foot guards for your safety!

Heavy-duty table trolley with 2 load surfaces, RAL 7016

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.504/AG	1040	500	880	850	500	34.0	400	160 x 40
sw-600.510/AG	1190	600	920	1000	600	40.5	500	200 x 40
sw-700.500/AG	1190	700	920	1000	700	46.0	500	200 x 40
sw-800.500/AG	1390	800	920	1200	800	51.5	500	200 x 40

Load capacity shelf: 200 kg*

EasySTOP swivel castors and foot guards for your safety!



*Static distributed load; Total load of the transport device must not be exceeded!

Tubular steel trucks

Tubular steel trucks

Welded steel construction; With 2 innovative plastic safety handles; Toe of sheet steel; With bended transverse struts; Trucks powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Pneumatic tyres on steel wheel rim or solid-rubber tyres on special plastic wheel rim with precision deepgroove ball bearings and plastic wheel cap.



Tubular steel truck, RAL 7035

Article no.	Dimension mm			Toe plate mm		Weight kg	Load cap. kg	Wheel diam. mm	
	W	D	H	w	d				
sk-710.015/LG	P	570	530	1105	320	250	12.5	200	260 x 85
sk-710.016/LG	SR	570	530	1105	320	250	14.5	200	260 x 65

P = Pneumatic tyres, SR = Solid-rubber tyres

Pushbar trolley, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.100/LG	975	500	975	880	500	25.0	400	160 x 40
sw-600.100/LG	1125	600	1015	1030	600	29.5	500	200 x 40
sw-700.100/LG	1125	700	1015	1030	700	33.5	500	200 x 40
sw-800.100/LG	1325	800	1015	1230	800	37.0	500	200 x 40

EasySTOP swivel castors and foot guards for your safety!



Heavy-duty table trolleys

Heavy-duty table trolleys

Modular system; Base structure with innovative frame section; Load surfaces of wood-based board, surface coated in dark grey; Load surfaces flush with the frame; Trolleys powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard; 2 EasySTOP swivel castors and 2 fixed castors.



Heavy-duty table trolley with 2 load surfaces, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.504/LG	1040	500	880	850	500	34.0	400	160 x 40
sw-600.510/LG	1190	600	920	1000	600	40.5	500	200 x 40
sw-700.500/LG	1190	700	920	1000	700	46.0	500	200 x 40
sw-800.500/LG	1390	800	920	1200	800	51.5	500	200 x 40

Load capacity shelf: 200 kg*

EasySTOP swivel castors and foot guards for your safety!



*Static distributed load; Total load of the transport device must not be exceeded!



Light table trolleys

Modular system; Base structure with innovative frame section; Load surfaces of wood-based board, surface coated in dark grey; Set in angle-steel frame, edge = 15 mm high; Trolleys powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard; 2 **EasySTOP** swivel castors and 2 fixed castors.



Table trolley with 2 load surfaces, RAL 7016

Article no.	Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.501/AG	1025	525	850	835	495	28.0	250	125 x 32
sw-600.501/AG	1175	625	850	985	595	33.5	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



Table trolley with 3 load surfaces, RAL 7016

Article no.	Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.603/AG	1025	525	850	835	495	37.0	250	125 x 32
sw-600.601/AG	1175	625	850	985	595	44.5	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!

Table trolley with 2 load surfaces, RAL 7016

Article no.	Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.500/AG	975	525	1010	835	495	28.5	250	125 x 32
sw-600.500/AG	1125	625	1010	985	595	34.0	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



Table trolley with 3 load surfaces, RAL 7016

Article no.	Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.600/AG	975	525	1010	835	495	37.5	250	125 x 32
sw-600.600/AG	1125	625	1010	985	595	45.0	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



*Static distributed load; Total load of the transport device must not be exceeded!

Light table trolleys



Table trolley with 2 load surfaces, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.501/LG	1025	525	850	835	495	28.0	250	125 x 32
sw-600.501/LG	1175	625	850	985	595	33.5	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



Table trolley with 3 load surfaces, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.603/LG	1025	525	850	835	495	37.0	250	125 x 32
sw-600.601/LG	1175	625	850	985	595	44.5	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



Table trolley with 2 load surfaces, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.500/LG	975	525	1010	835	495	28.5	250	125 x 32
sw-600.500/LG	1125	625	1010	985	595	34.0	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!



Table trolley with 3 load surfaces, RAL 7035

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	W	D	H	w	d			
sw-500.600/LG	975	525	1010	835	495	37.5	250	125 x 32
sw-600.600/LG	1125	625	1010	985	595	45.0	250	125 x 32

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!

*Static distributed load; Total load of the transport device must not be exceeded!




Shelf trolleys fixed welded

Fixed welded angle-steel construction; Trolleys with double wing doors have espagnolette bolt lock with T-handle; Double wing door with cylinder lock, incl. 2 keys (different locking); Push/pullbar and double wing door are flush with the frame when not in use; Push/pullbar with soft plastic grip cover black; End and side walls, roof and doors with mesh sides 50 x 50 mm; Load surface and shelves of wood-based board, surface coated in dark grey; Shelf supports for variable insertion at 50 mm intervals; Trolleys powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard; 2 **EasySTOP** swivel castors and 2 fixed castors.



The push/pullbar is flush with the frame when not in use.



The push/pullbar adjusts to the height of the person pulling when the trolley is being pulled.



T-handle lock


Shelf trolley fixed welded, RAL 7016

Article no.	Dimension mm			Loading surface mm		Weight kg	Load cap. kg	Wheel diam. mm
	w	D	H	w	d			
sw-700.987/AG	1115	730	1810	1045	685	117.5	500	200 x 40
sw-800.987/AG	1315	830	1810	1245	785	140.0	500	200 x 40

Load capacity shelf: 80 kg*
EasySTOP swivel castors and foot guards for your safety!

*Static distributed load; Total load of the transport device must not be exceeded!

Shelf trolleys fixed welded



The double wing door opens 270° and is flush with the frame.



The push/pullbar rests on the cross tube when pushing. This ensures that pushing is safe and comfortable.

Shelf trolley fixed welded, RAL 7035

Article no.	Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
	w	D	H	w	d			
sw-700.987/LG	1115	730	1810	1045	685	117.5	500	200 x 40
sw-800.987/LG	1315	830	1810	1245	785	140.0	500	200 x 40

Load capacity shelf: 80 kg*

EasySTOP swivel castors and foot guards for your safety!



Additional articles - Shelves of wood-based board for shelf trolleys, RAL 7016/7035

Article no.	Dimension		for loading surface		Weight kg	Load cap. kg	
	w	D	w	d			
zsw-700.411/G	1030	660	1045	685	11.5	80	Additional shelf
zsw-800.411/G	1230	760	1245	785	16.0	80	

*Static distributed load; Total load of the transport device must not be exceeded!



Steel-frame dollies for pallets

Welded steel construction; Suitable for Euro pallets or cage pallets; Incl. locating cups; Dollies powder-coated RAL 7016 anthracite grey or RAL 7035 light grey; Permanent surface protection; Impact- and scratch-resistant; Grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard or elastic solid-rubber tyres on cast aluminium wheel rim with precision deepgroove ball bearings with foot guard; 2 **EasySTOP** swivel castors and 2 fixed castors.



Steel-frame dolly, RAL 7016

Article no.		Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
		W	mm D	H	w mm	d			
sw-870.041/AG	TR	870	670	350	810	610	25.0	500	200 x 40
sw-870.015/AG	TR	1070	870	350	1010	810	28.0	500	200 x 40
sw-870.000/AG	TR	1270	870	350	1210	810	32.0	500	200 x 40
sw-870.020/AG	TR	1270	1070	350	1210	1010	32.5	500	200 x 40

EasySTOP swivel castors and foot guards for your safety!
TR = Thermoplastic rubber tyres



Steel-frame dolly, RAL 7016

Article no.		Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
		W	mm D	H	w mm	d			
sw-870.042/AG	ER	870	670	350	810	610	29.5	1200	200 x 50
sw-870.036/AG	ER	1070	870	350	1010	810	32.5	1200	200 x 50
sw-870.001/AG	ER	1270	870	350	1210	810	35.5	1200	200 x 50
sw-870.501/AG	ER	1270	1070	350	1210	1010	37.5	1200	200 x 50

EasySTOP swivel castors and foot guards for your safety!
ER = Elastic solid-rubber tyres



Steel-frame dollies for pallets



Steel-frame dolly, RAL 7035

Article no.		Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
		w	D	H	w	d			
sw-870.041/LG	TR	870	670	350	810	610	25.0	500	200 x 40
sw-870.015/LG	TR	1070	870	350	1010	810	28.0	500	200 x 40
sw-870.000/LG	TR	1270	870	350	1210	810	32.0	500	200 x 40
sw-870.020/LG	TR	1270	1070	350	1210	1010	32.5	500	200 x 40

EasySTOP swivel castors and foot guards for your safety!
TR = Thermoplastic rubber tyres



Steel-frame dolly, RAL 7035

Article no.		Dimension			Loading surface		Weight kg	Load cap. kg	Wheel diam. mm
		w	D	H	w	d			
sw-870.042/LG	ER	870	670	350	810	610	29.5	1200	200 x 50
sw-870.036/LG	ER	1070	870	350	1010	810	32.5	1200	200 x 50
sw-870.001/LG	ER	1270	870	350	1210	810	35.5	1200	200 x 50
sw-870.501/LG	ER	1270	1070	350	1210	1010	37.5	1200	200 x 50

EasySTOP swivel castors and foot guards for your safety!
ER = Elastic solid-rubber tyres



www.**VARIO***fit*.eu

Cordes GmbH & Co. KG

Weißfelder Straße 1

D - 21698 Harsefeld

tel.: +49 (0) 4164 816 0

fax: +49 (0) 4164 816 28 300

email: info@cordes.eu

info@variofit.eu

Transport Systems